

GESPASA EA- 90 12 or 24 VDC

The self-suction gear pumps are suitable for all type of oil supplies and admit the hose-reel coupling in the delivery. This pump is suitable for its use in the agriculture, building, public works, industry. It supplies oil up to 2.5 m suction from aerial or buried tanks.

EA-90 12 or 24 VDC

0.37 kW · 20-25 l/min

 LUBRICANT



EA-90 12 VDC 20-25 l/min

03014-CF00000

EA-90 24 VDC 20-25 l/min

03090-CF00000

The self-suction gear pumps are suitable for all type of oil supplies and admit the hose-reel coupling in the delivery.

This pump is suitable for its use in the agriculture, building, public works, industry,...

It supplies oil up to 2.5 m suction from aerial or buried tanks.

Technical data:

- With recirculation bypass system
- It is suitable for lubricant transfer with average/low density
- Suction: 2.5 m · Delivery: 40 m
- Flow: 20-25 l/min (SAE-20/50W at 25°C)
- Motor: 0.37 kW self-ventilated 12 or 24 VDC
- S1 continuous duty
- IP-55 protection
- Consumption: 35-55 A (12 VDC) and 20-32 A (24 VDC)
- 1,500 rpm
- Bypass tared at 5-6 bar
- Inlet/outlet tube: 1/2" GAS (BSP)
- With clamps for 12 or 24 VDC battery connection with 2 m of cable